



To mount, place the Stepped Plate (5) under the lathe bed at a spot that will allow you to slide it into final position. Place the Adjustable Connection Plate (4) above it and thread the 3-Star Knob with 1½" Bolt (8) into the Stepped Plate (5).

### PARTS LIST - LATHE DUST COLLECTION SYSTEM

|   | Quantity |
|---|----------|
| 1 Dust Scoop                                | 1        |
| 2 Port Boom Arm                             | 1        |
| 3 Post                                      | 1        |
| 4 Adjustable Connection Plate               | 1        |
| 5 Stepped Plate                             | 1        |
| 6 2½" FlexForm™ Dust Hose                   | 1        |
| 7 Hose Clamp                                | 1        |
| 8 3-Star Knob with 1½" Bolt                 | 1        |
| 9 3/8"-16 x 1" Screw                        | 1        |
| 10 Rubber Washer                            | 1        |
| 11 3-Star Knob with Threaded Insert         | 1        |
| 12 3-Star Knob with 5/8" Bolt and Nylon Tip | 1        |
| 13 Plastic Washer                           | 2        |



## Turning

Position the bottom edge of the Dust Scoop against the lathe tool rest. This helps channel the suction for maximum dust removal.



## Sanding

Reposition the Dust Scoop to ensure your fingers won't get trapped between it and the workpiece.

Check Rockler.com for updates. If you have further questions, please contact our Technical Support Department at 1-800-260-9663 or support@rockler.com

003

### Important Safety Instructions

1. This tool is designed for specific applications as defined in the instructions and should not be modified and/or used for any other applications.
2. Before using the Rockler Dust Right Lathe Dust Collection System read, understand and follow all instructions and safety information provided.
3. For any tool that is used in conjunction with this product always read, understand and follow the instructions and safety warnings for that tool.
4. Before using this product, review and verify that all tools used with it are in proper working order as defined by the tool's owner's manual.
5. All safety equipment must be installed and working properly as defined by the tool's owner's manual.
6. Do not use this product until you have read the provided instructions and warnings and are confident you understand them.
7. Always wear safety glasses in compliance with ANSI safety standards and hearing protection and follow all standard shop safety practices including:
  - A. Keep your work area well lit and clean.
  - B. Use dust collection tools and dust face masks to reduce exposure to dust.
  - C. Keep children and bystanders away while operating your tools.
  - D. Maintain proper footing at all times and do not overreach.
  - E. Do not force the tool.
  - F. Unplug all power tools before making any adjustments or changing accessories.
8. Remain alert and use good judgment when using this tool. Do not use this tool if you are in any way impaired by medications, alcohol, drugs or fatigue.
9. Dress appropriately and remove all jewelry, secure loose clothing and tie up long hair before using this tool.
10. It is the sole responsibility of the purchaser of this tool to ensure that any third party reads and agrees to all the safety precautions outlined in this manual prior to using the tool.
11. Maintain these instructions and warnings as long as you own the tool. Keep in a place where they will be readily available for reference.
12. The user assumes all risk for the proper use of this tool and for ensuring product suitability for intended application.
13. These warnings and instructions do not represent the total of all information available regarding tool safety, use and technique. Always seek out opportunities to learn more and improve your skills and knowledge.
14. Before turning on the lathe, verify that all of the Lathe Dust Collection System components are installed properly and are securely tightened.
15. With the lathe off, hand-spin your workpiece to ensure that it will not come into contact with any part of the Lathe Dust Collection System.
16. While sanding, the lathe tool rest must be removed.
17. While sanding, keep the Dust Scoop in the sanding position (Dust Scoop is tilted vertically – i.e., not surrounding the workpiece but behind it) to prevent finger entrapment.
18. Always use sharp tools and practice proper woodturning technique.
19. Use the appropriate lathe speed for the work being done, as defined by your lathe manufacturer.
20. Be aware that, with your dust collection unit on, sand paper or rags may be drawn toward the Dust Scoop. Maintain awareness and use a secure grip.